

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification <sup>6</sup> : <b>G01N 27/447</b>	<b>A1</b>	(11) International Publication Number: <b>WO 99/64851</b> (43) International Publication Date: 16 December 1999 (16.12.99)
---	-----------	---

(21) International Application Number: PCT/US99/13340  
(22) International Filing Date: 11 June 1999 (11.06.99)  
(30) Priority Data:  
60/088,956 11 June 1998 (11.06.98) US  
(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application  
US 60/088,956 (CIP)  
Filed on 11 June 1998 (11.06.98)  
(71) Applicant (for all designated States except US): ARIZONA BOARD OF REGENTS [US/US]; Arizona State University, Box 873211, Tempe, AZ 85287 (US).  
(72) Inventors; and  
(75) Inventors/Applicants (for US only): HAYES, Mark, A. [US/US]; 3583 W. Barcelona Drive, Chandler, AZ 85226 (US). POLSON, Nolan, A. [US/US]; 1300 W. Shannon Street, Chandler, AZ 85224 (US).  
(74) Agents: SORELL, Louis, S. et al.; Baker & Botts, LLP, 30 Rockefeller Plaza, New York, NY 10112-0228 (US).

(81) Designated States: CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

**Published**  
With international search report.

(54) Title: CONTROL OF FLOW AND MATERIALS FOR MICRO DEVICES



(57) Abstract

The present invention generally relates to methods and devices for the control of the movement of fluids and electrically charged sample components within those fluids. More particularly, the present invention permits exclusion or concentration of specifically chosen sample components within a fluid. The present invention provides an analytical device, either microchip- or capillary-based, having the means to exclude specific sample components of interest from a capillary or channel for the purpose of preconcentration or control of movement of sample components. Such a control system includes a means for controlling the flow of the fluid in the channel and the placement of an electrode at the immediate entrance of each channel on such devices so that material may be directly manipulated by effects of both bulk flow and electrically driven migration.